



Model: **AM4113ZTL** Dino-Lite Premier

SPECIFICATIONS

Model	AM4113ZTL Dino-Lite Premier	Microtouch	Touch sensitive trigger on the microscope for taking picture
Interface	USB 2.0	Lighting	8 White LED light switched On/Off by software
Product Resolution	1.3M pixels (SXGA)	Polarizer	Yes
Magnification Rate	20x - 90x	Measurement Function	Yes
Sensor	Color CMOS	Calibration Function	Yes
Frame Rate	Up to 30fps	Operating System Supported	Window 10, 8, 7, Vista, XP MAC OS 10.4 or later
Save Formats	Image DinoCapture 2.0 : BMP, GIF, PNG, MNG, TIF, TGA, PCX, WBMP, JP2, JPC, JPG, PGX, RAS, PNM DinoXcope : PNG, JPEG Movie DinoCapture 2.0 : WMV, FLV, SWF DinoXcope : MOV	Unit Weight	105g
		Unit Dimensions	10.5cm (H) x 3.2cm (D)
		Package Dimensions	16cm (L) x 16cm (W) x 6cm (H)

HIGHLIGHTS



Enhanced 1.3 Megapixels



USB 2.0 Interface



**Professional
Measurement Tools**



Long Working Distance



Scroll Lock


PRODUCT SUMMARY

Featuring rotatable polarization, working distance optics, and enhanced 1.3 Megapixels sensor.

GALLERY



Repairing



More FOV



Inspection




Inspection



IC



Crystalline rock



Component