

DINO - LITE *Edge*

Model: **AM7115MZTL** Dino- Lite Edge

SPECIFICATIONS

Model	AM7115MZTL Dino-Lite Edge	System Requirements	<ul style="list-style-type: none"> Intel Core2 Duo @ 2.20 GHz / AMD Athlon X2 Dual Core BE-2400 (2.3GHz) 20GB available HD Space 2GB available RAM or more 512MB video card or more CD-ROM drive for installation USB 2.0
Interface	USB 2.0		
Product Resolution	5M pixels (2592 x 1944)		
Magnification	10x - 140x		
Frame Rate	10fps in 5MP / 3MP/ 2MP, MJPEG 25fps in 1.3MP, MJPEG 30fps in VGA, MJPEG	Calibration Function	Yes
Lighting	8 white LEDs	Measurement Function	Yes
Microtouch	Yes	Unit Dimensions	10.5cm (H) x 3.2cm (D)
Operating System Supported	Window 10, 8, 7, Vista, XP MAC OS 10.4 or later	Unit Weight	125g

HIGHLIGHTS



High Optical Resolution



5.0 Megapixels



Flexible LED Control (FLC)



Adjustable Polarizer



Robust Housing



Long Working Distance (LWD) Optics



Scroll Lock



Interchangeable Caps

PRODUCT SUMMARY

Dedicated to provide ample space for working under, the AM7115MZTL, a Long-Working-Distance(LWD) version of Dino-Lite 5MP Edge series, delivers superior image at 10x-140x magnification with greatest illumination flexibility.

The AM7115MZTL is able to provide long working distance with fluent and crisp live image through the use of cutting-edge optics, advanced 5MP sensor, and low-loss MJPEG compression. The innovative Flexible LED Control (FLC) enables partial illumination to enhance edge contrast and provides intensity adjustability for better adaptability. Together with adjustable polarizer, interchangeable front caps, rugged metal housing, the AM7115MZTL is made to be the tool of choice for wide range of applications.