

# Dino-Lite Edge



Model: **AM7915MZTL**

SPECIFICATIONS			
Model	AM7915MZTL Dino-Lite Edge	OS Supported	Windows 10, 8, 7, Vista, XP Mac OS 10.12 ~ 10.14 (EDOF/EDR are NOT controllable on Mac OS)
Interface	USB 2.0		
Product Resolution	5M pixels (2592x1944)	Frame Rate	10fps in 5MP/3MP/2MP, MJPEG 25fps in 1.3MP, MJPEG 30fps in VGA, MJPEG
Magnification	10x~140x		
Calibration Function	Yes	System Requirements	<ul style="list-style-type: none"> <li>· Intel Core2 Duo @ 2.20 GHz/AMD Athlon X2 Dual Core BE-2400 (2.3GHz)</li> <li>· 20GB available HD space</li> <li>· 4GB available RAM or more</li> <li>· 2GB video card or more</li> <li>· CD-ROM drive for installation</li> <li>· USB 2.0</li> </ul>
Measurement Function	Yes		
Microtouch	Yes		
Lighting	8 white LEDs		
Unit Dimension	10.5cm (H) x 3.2cm (D)		
Unit Weight	138g		

## HIGHLIGHTS



High optical resolution



5.0 Megapixels



Flexible LED Control



Automatic Magnification Reading



Robust Housing



Extended Depth of Field



Extended Dynamic Range



Adjustable polarizer



Scroll Lock



Interchangeable caps



Long-Working-Distance (LWD) optics

## PRODUCT SUMMARY

The 5MP Edge AM7915MZTL, a long-working-distance model, has perfectly merged with AMR and EDOF/EDR which makes it ideal for most professional needs, yet its stunningly image quality and illumination flexibility suites well for various imaging task.

Note: EDOF/EDR available on Windows PC only.



Dpro Vision Sdn Bhd  
B-08-03, Dataran 32, No.2, Jalan 19/1, 46100 Petaling Jaya, Selangor.  
Tel : 03-7960 4710 / Email : sales@dprovision.com / Website : www.dprovision.com

