

AF4515-FIT Dino-Lite Edge



Model: **AF4515-FIT**

SPECIFICATIONS

Model	AF4515-FIT Dino-Lite Edge	OS Supported	Windows 10, 8, 7, Vista, XP Mac OS 11.6 or later
Interface	USB 2.0	Frame Rate	15fps in 1.3MP, MJPEG 30fps in VGA, MJPEG
Product Resolution	1.3M pixels (1280x1024)	Save Formats	Image: DinoCapture2.0: BMP, GIF, PNG, MNG, TIF, TGA, PCX, WBMP, JP2, JPC, JPG, PGX, RAS, PNM DinoXcope: PNG, JPEG Video: DinoCapture2.0: WMV, FLV, SWF DinoXcope: MOV
Magnification	20x~220x		
Calibration Function	Yes		
Measurement Function	Yes		
Microtouch	Yes		
Lighting	8 Infrared LEDs		
Unit Dimension	11.4cm (H) x 3.3cm (D)		
Unit Weight	111g		

HIGHLIGHTS



850nm IR illumination



1.3 Megapixels



Adaptable interface



Adjustable LED intensity



Automatic Magnification Reading



Scroll Lock



Interchangeable caps

PRODUCT SUMMARY

Equipped with an 850 nm light, AF4515-FIT is suitable for examining targets with infrared transmissive or reflective surfaces. This model is compatible with WF-20 Wi-Fi streamer to transform AF4515-FIT into a wireless digital microscope.



Dpro Vision Sdn Bhd
B-08-03, Dataran 32, No.2, Jalan 19/1, 46100 Petaling Jaya, Selangor.
Tel : 03-7960 4710 / Email : sales@dprovision.com / Website : www.dprovision.com

