

Dino-Lite Edge^{PLUS}



Model: **AM4917MT8 Dino-Lite Edge^{PLUS}**

SPECIFICATIONS			
Model	AM4917MT8 Dino-Lite Edge ^{PLUS}	Frame Rate	30 fps in 1.3 MP, MJPEG 30 fps in VGA, MJPEG
Interface	USB 2.0	Operating System Supported	Windows 7/8/10/11 macOS 10.14 or later
Product Resolution	1.3 MP (1280 x 960)	Saving Format	Image: DinoCapture2.0: BMP, GIF, PNG, MNG, TIF, TGA, PCX, WBMP, JP2, JPC, JPG, PGX, RAS, PNM DinoXscope: PNG, JPEG Video: DinoCapture2.0: WMV, FLV, SWF DinoXscope: MOV
Magnification Rate	700x ~ 900x		
Lighting	8 white LEDs		
Microtouch	Yes		
Calibration Function	Yes		
Measurement Function	Yes		
Unit Weight	130g		
Unit Dimension	10.7 cm (H) x 3.3 cm (D)		

HIGHLIGHTS



1.3 Megapixels



Extended Depth of Field



Depth Acquisition



Enhanced Flexible LED Control



Extended Dynamic Range



Scroll Lock



Metal Housing



Automatic Magnification Reading

PRODUCT SUMMARY

At high magnifications, the thickness or roughness of targets may impede obtaining clear images. EdgePLUS AM4917MT8's high-sensitivity sensor, combined with the EDOF feature, generates high-quality focused-stacked images of targets at 800x magnification. AM4917MT8 offers DPQ, eFLC, AMR, EDR, and even a click-to-focus function to ease finding focus on a point of interest.

Note: EDOF, EDR, and DPQ are available on Windows PC only.



Dpro Vision Sdn Bhd
B-08-03, Dataran 32, No.2, Jalan 19/1, 46100 Petaling Jaya, Selangor.
Tel : 03-7960 4710 / Email : sales@dprovision.com / Website : www.dprovision.com

